

Teaching & Learning
Step-by-Step Guide:

Environmental Problem Mapping



Chethika Abenayake

Harini Sawandi

Samith Madusanka

Teaching & Learning Step by -Step Guide: Environmental Problem Mapping

Authors

Chethika Abenayake

Harini Sawandi

Samith Madusanka

Publisher

University of Moratuwa

Author contribution

1. Chethika Abenayake (Supervision, Conceptualisation, Methodology, Validation), Department of Town & Country Planning, University of Moratuwa, Sri Lanka.
2. Harini Sawandi (Formal Analysis, Writing—original draft preparation), Department of Town & Country Planning, University of Moratuwa, Sri Lanka.
3. Samith Madusanka (Project Administration, Review and Editing), Department of Town & Country Planning, University of Moratuwa, Sri Lanka.

All authors have read and agreed to the published version of the book.

Contact authors chethika@uom.lk,

This book was produced with the valuable support of the Erasmus+ Capacity Building in Higher Education (CBHE) project 'Curricula Enrichment for Sri Lankan Universities delivered through the application of Location-Based Services to Intelligent Transport Systems' (LBS2ITS <https://lbs2its.net/>)

Project Number: 618657-EPP-1-2020-1-AT-EPPKA2-CBHE-JP

Programme: Erasmus+

Key Action: Cooperation for innovation and the exchange of good practices

Action Type: Capacity Building in Higher Education

Co-funding: Erasmus+ Programme of the European Union

This book was reviewed as an Open Education Resource for University students by Prof. Retscher Günther (Vienna University of Technology, Austria) under the LBS2ITS project.



LBS2ITS
Curricula Enrichment delivered through
the Application of Location-based Services
to Intelligent Transport Systems



lbs2its.net

Co-funded by the
Erasmus+ Programme
of the European Union



Edition

First Edition - May 2025

Copyright

Teaching & Learning Step-by-Step Guide: Environmental Problem Mapping © 2025 by Chethika Abenayake, Harini Sawandi, Samith Madusanka is licensed under Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International. To view a copy of this license, visit <https://creativecommons.org/licenses/by-nc-nd/4.0>.

Some Rights Reserved

ISBN 978-955-9027-90-4 (ebook)

Citation

Abenayake, C., Sawandi, H., & Madusanka, S. (2025). *Teaching & learning step-by-step guide—Environmental problem mapping* (1st ed.). University of Moratuwa.

Disclaimer

This publication is designed to provide accurate and authoritative information in regard to the subject matter covered. The contents and views in this publication do not necessarily reflect the views of the publisher.

Publisher

University of Moratuwa

PREFACE

This book serves as open educational material for both undergraduate and postgraduate degree programs, offering a detailed, step-by-step guide to GPS and GNSS data collection using modern devices such as the Stonex S70 and S70G tablets. Designed to bridge the gap between theoretical knowledge and practical application, this guide is meticulously crafted to meet the needs of students, educators, and practitioners alike.

Within the book, readers will find comprehensive instructions on setting up and configuring smartphone and GNSS devices, collecting high-accuracy spatial data, and employing GIS software to analyze this information. It covers various applications, including tree mapping, urban planning, environmental monitoring, and more. The book not only enhances learning in academic settings by providing real-world applications and case studies but also equips industry professionals with the skills necessary to conduct advanced spatial analysis and contribute meaningful insights in their fields.

Key topics include detailed steps on initializing and configuring GNSS devices to ensure optimal accuracy and reliability, along with guidelines on effective field data collection to achieve high-quality GNSS data. The book provides comprehensive instructions on downloading, processing, and managing collected data using GIS software. It features real-world examples and case studies that demonstrate the practical applications of GNSS data collection, as well as techniques for analyzing spatial data to derive meaningful insights and support decision-making processes.

Whether you are a student aiming to master GNSS and smartphone data collection and geographic information systems, a teacher looking for robust educational tools, or a practitioner in need of refining your technical expertise, this book offers invaluable guidance and support. It ensures that users at all levels gain proficiency in leveraging modern technologies to explore and solve geographic challenges effectively.

TABLE OF CONTENT

TABLE OF CONTENT	vi
LIST OF FIGURES	vii
1. INTRODUCTION	1
1. OVERVIEW OF ENVIRONMENTAL MAPPING AND ITS SIGNIFICANCE	2
2. REQUIRED TOOLS / SOFTWARE AND EQUIPMENT	3
3. DATA COLLECTION	4
4.1 Different between Smartphone (Global Positioning System) and Global Navigation satellite system	4
4.2 Data Collection using Smartphones (Global Positioning System).....	6
4.2.1 Overall Data Collection Process	6
4.3 Steps (Mobile Phones).....	9
4.4 Data Collection using GNSS (Global Navigation Satellite System).....	26
4.4.1 Overall Data Collection Process	26
4.4.2. S70 G Data Collection	27
4.4.3.S70 Data Collection	62
5. MEASURE AND MAP NOISE POLLUTION WITH MOBILE PHONE	103
5.1 Introduction.....	103
5.2 Overview of Mobile Apps for Noise Measurement.....	104
5.2.1 Features of Noise Capture App:	104
5.2.3 Architecture Diagram and Workflow	105
5.3 Steps	107

LIST OF FIGURES

Figure 1- Overview of the Environment	2
Figure 2 - Process of Data Collection	6
Figure 3- Interface of the Kobo Tool Box.....	9
Figure 4 - Create Account.....	10
Figure 5 - Registration Process	10
Figure 6 - Create a New Data Collection Form	11
Figure 7 - Interface of Create a new project	11
Figure 8 - Create Project.....	12
Figure 9 - Project Interface	12
Figure 10 - Add Question Interface.....	12
Figure 11 - Insert Questions	13
Figure 12 - Selecting Type of the Questions	13
Figure 13 - Proceed to the next Questions	14
Figure 14 - Save the Project	14
Figure 15 - Preview the Project	14
Figure 16 - Redirected to the project page	14
Figure 17 - Created Form	15
Figure 18 - Deploy.....	16
Figure 19 - Download and Install the app.....	16
Figure 20 - Interface of the ODK Figure 21 - ODK Details	18
Figure 22 - Kobo Toolbox	19
Figure 23 - Link the Form Figure 24 - New Interface.....	19
Figure 25 - Download the Form	20
Figure 26- Collect Data	20

Figure 27 - Data Exporting Process.....	21
Figure 28 - Collected Data	22
Figure 29 - Data Downloading	22
Figure 30 - Excel File	23
Figure 31 - Add Data to QGIS	24
Figure 32 - Collected Data point of trees.....	24
Figure 33 - Edit the Data.....	25
Figure 34 - Share the Details	25
Figure 35 -Data Collection from GNSS	26
Figure 36 - Two types of S70G.....	27
Figure 37 -Cube a v6	28
Figure 38 -Project Manager	29
Figure 39 - Create New File.....	30
Figure 40 -Create Project.....	31
Figure 41 - Set Coordinates.....	32
Figure 42 -Stonex Cube.....	33
Figure 43 - Coordinate Systems	34
Figure 44 - Set the Coordinates.....	35
Figure 45 - Set up the Device	36
Figure 46 - Disconnecting	37
Figure 47 - Connect the Device	38
Figure 48 -Working Mode	39
Figure 49 - Select Rover	40
Figure 50 - Setting the Rover.....	41
Figure 51 -Enable the GPS.....	42

Figure 52 -Get Access Point.....	43
Figure 53 -Select the point.....	44
Figure 54 - Finalize the Rover Setup	45
Figure 55 -Setup the Antenna.....	46
Figure 56 - Select the Antenna Type	47
Figure 57 - Point Survey	48
Figure 58 -Survey Map	49
Figure 59 -Topo Point	50
Figure 60 - Quality Check	51
Figure 61 -Map Page	52
Figure 62 -Get the point.....	53
Figure 63 - Save the Point	54
Figure 64- Collected Point	55
Figure 65 - Point Library	56
Figure 66 - Export Data.....	57
Figure 67 -Click Export	58
Figure 68 - Export Formats	59
Figure 69 -User Action	60
Figure 70 -Share	61
Figure 71 -Cube a v6	62
Figure 72 -Project Manager	63
Figure 73 -Create New File.....	64
Figure 74 --Create Project	65
Figure 75 -Enable GIS	66
Figure 76 -Set Coordinates.....	67

Figure 77 -Stonex Cube	68
Figure 78 - Coordinate Systems	69
Figure 79 -Set the Coordinates.....	70
Figure 80 - Tree Mapping Sub-Category.....	71
Figure 81 -Naming	72
Figure 82 -Activate GIS Features	73
Figure 83 -Edit.....	74
Figure 84 -ADD	75
Figure 85 -Edit GIS Features	76
Figure 86 - Edit GIS Features	77
Figure 87 - Edit GIS Features	78
Figure 88 -Set GIS Features.....	79
Figure 89 – User Action Required	80
Figure 90 -Set Repository	81
Figure 91 -User Action	82
Figure 92 -Set Gis and Repository	83
Figure 93 -Set up the Device	84
Figure 94 - Disconnecting	85
Figure 95 -Connect the Device	86
Figure 96 -Working Mode	87
Figure 97 -Rover	88
Figure 98- Set the parameters.....	89
Figure 99- Enable the following satellite system	90
Figure 100-Point Survey	91
Figure 101 -Map page.....	92

Figure 102 --Get the point.....	93
Figure 103-Topo point.....	94
Figure 104- Add description.....	95
Figure 105-Enter GIS attributes.....	96
Figure 106 - Collect the data	97
Figure 107- Point Library	98
Figure 108 -Export Data.....	99
Figure 109 -Exporting	100
Figure 110 -Export Format.....	101
Figure 111 -Export	102
Figure 112 -Noise Capture App.....	104
Figure 113 - Work Process	105
Figure 114 - Install the app	107
Figure 115 - Setup the app	108
Figure 116 -3 Main Tabs.....	109
Figure 117. Recording	110
Figure 118 -Stop the Recording.....	110
Figure 119 -Validate.....	111
Figure 120 -Result.....	112
Figure 121 -Map Features	113
Figure 122 -Export Data.....	113
Figure 123 - Add to QGIS	116
Figure 124- Add Symbology	116

1. INTRODUCTION

This book offers comprehensive guidance for individuals and groups engaged in evaluating and tackling environmental issues employing gathering and analyzing spatial information. This guidebook provides users with the required tools and approaches to map and comprehend environmental problems in their communities by utilizing GPS and GNSS technology, as well as open-source applications including QGIS.

Because of the growing environmental issues the world is confronting, such as climate change, biodiversity depletion, pollution, and habitat destruction, the demand for accurate and feasible data has become exceedingly crucial. Environmental problem mapping is an essential initial process in recognizing, ranking, and addressing environmental concerns, facilitating well-informed decision-making and focused solutions.

Smartphone / GPS (Global Positioning System) and GNSS (Global Navigation Satellite System) technologies are crucial for mapping environmental problems. They enable users to gather accurate position data while in the field. Through the utilization of GPS/GNSS data-gathering techniques, individuals can precisely record environmental observations, monitor variations over a period, and pinpoint areas of concern with spatial detail.

This book is intended for a wide range of readers, who are interested in tackling environmental issues at the local, regional, or global level. Our goals are to equip users with the information and abilities needed to carry out efficient environmental problem mapping projects

The book is structured into three chapters, each focusing on key aspects of environmental problem mapping:

Chapter 2 - Overview of environmental mapping.

Chapter 3 - Detailed methodology for data collection, analysis, and interpretation using GPS

Chapter 4- Detailed methodology for data collection, analysis, and interpretation using GNSS technologies and open-source software.

1. OVERVIEW OF ENVIRONMENTAL MAPPING AND ITS SIGNIFICANCE

Environmental mapping involves the systematic **collection, analysis, and visualization of spatial data** to understand and address environmental issues.




Figure 1- Overview of the Environment

Source - <https://www.edrawmind.com/article/environment-mind-map.html>

Environmental mapping provides a comprehensive perspective on environmental conditions and trends, including recording changes in land cover and vegetation, monitoring pollution levels, and assessing habitat loss. This comprehensive understanding allows us to pinpoint areas that cause concern, such as locations with high levels of pollution, the breaking up of habitats, and ecosystems that are at risk, and want immediate attention and intervention. Furthermore, environmental mapping facilitates evidence-driven decision-making and policy development by supplying policymakers with information and spatial analysis to inform the allocation of resources, land-use planning, and environmental management methods. Environmental mapping facilitates the communication of intricate environmental data in a visually comprehensible manner. Additionally, it encourages the involvement of stakeholders, enhances transparency, and encourages collaborative efforts towards achieving sustainable environmental management.

2. REQUIRED TOOLS / SOFTWARE AND EQUIPMENT






Category	GPS Data collection	GNSS Data Collection
Equipment	 Smartphone (Android or iOS)	 Stonex S70 / S70G GNSS Receiver
Software/Apps	 <p>ODK Collect, KoBoToolbox: (These apps allow users to create custom forms, collect GPS coordinates, and input field data efficiently)</p>  QGIS (open-source GIS software used for data analysis and visualization post-data collection, offering powerful tools for spatial analysis and mapping.)	<p>(Data collection is done with the device itself)</p>  QGIS (for data analysis)
Other Tools and Inputs	<ul style="list-style-type: none"> • Base Map of the Site: A base map provides contextual information about the area you are mapping, such as existing infrastructure, land cover, and topographic features • Field Equipment (If necessary): Depending on your project needs, you may require additional measuring tools such as tape measures, or surveying equipment for collecting site-specific data. • To ensure uninterrupted operation of your GPS/GNSS devices and smartphones, carry power banks or spare batteries for extended fieldwork sessions 	

Table 1 -Required Items

3. DATA COLLECTION

4.1 Different between Smartphone (Global Positioning System) and Global Navigation satellite system

- What are GPS and GNSS?

GPS stands for Global Positioning System, which is a satellite-based navigation system that provides location and time information anywhere on Earth. GNSS stands for Global Navigation Satellite System, which is a generic term that encompasses all satellite navigation systems, including GPS.

GPS receivers determine their location by utilizing a constellation of GPS satellites that orbit the Earth. The GPS was first developed for military applications, but it has since become accessible to civilian users. GPS has a wide range of applications, such as navigation, tracking, and mapping.

GNSS, short for "Global Navigation Satellite System," refers to any satellite navigation system utilized for positioning. GNSS, or Global Navigation Satellite System, encompasses various satellite navigation systems, of which GPS is one example. Additional Global Navigation Satellite Systems (GNSS) encompass the Russian GLONASS system, the European Galileo system, the Indian Regional Navigation Satellite System (IRNSS) known as NavIC (short for Navigation with Indian Constellation), and BeiDou, the Chinese system. Many GPS receivers are compatible with multiple GNSS systems, allowing them to utilize the unique benefits offered by each system.

- What are the disparities between the two?

GPS and GNSS are satellite-based technologies used to ascertain the precise location of a receiver on Earth. The Global Positioning System (GPS) is widely recognized as the most renowned navigation system, with a user base of millions of individuals who rely on it daily. GNSS is an all-encompassing system that encompasses GPS as well as other satellite constellations.



The number of satellites in a system can affect the accuracy of location information provided to users. GPS currently has 31 operational satellites in its network, while GLONASS has 24, Galileo has 30, BeiDou has 35, and QZSS has 7. Consequently, GNSS exhibits greater precision than GPS and can be employed in situations when GPS would be unsuitable. GNSS is commonly employed in aviation navigation to provide accurate positioning data of the aircraft. GPS is utilized in numerous consumer items, such as automotive navigation systems and mapping applications for smartphones. GNSS exhibits better resistance to disruption, making it a preferred choice for scenarios where GPS would be unsuitable.

- How can they be used in different applications?

GNSS/GPS applications include Tracking/Mapping Devices, Industrial Machinery, Sea vessels, Air Navigation etc.

Automobile GPS devices are becoming more and more common, whether they are separate from a phone or built into it. This gives them a very accurate idea of where they are. GPS can be used for a wide range of applications, such as navigation, tracking, and surveying. GNSS is a similar system that uses a network of satellites to figure out where something is. However, GNSS systems typically use more satellites than GPS, providing greater accuracy and coverage. GNSS is often used in mission-critical applications where high accuracy is required, such as aircraft and missile guidance systems.

- Pros and cons of GPS and GNSS

There are several pros and cons to GPS and GNSS. One advantage of GPS is that it is relatively inexpensive to set up and maintain. GPS is also widely available, with most smartphones now featuring GPS capabilities. Another advantage of GPS is that it can be used in a variety of settings, including urban and rural areas. One thing that can go wrong with GPS is that buildings and other things can interfere with it. A GPS signal can also be blocked by bad weather conditions. GNSS systems cost more than GPS systems, but they work better and are more accurate. Also, interference or bad weather is less likely to mess up GNSS systems.

In summary, while GPS is a specific satellite navigation system, GNSS encompasses multiple satellite navigation systems, including GPS. Many smartphones utilize GNSS technology, allowing them to access signals from multiple satellite systems to determine their precise location on Earth's surface. Therefore, smartphones with GPS functionality are a subset of devices that utilize GNSS technology for location determination

-
- <https://www.linkedin.com/pulse/differences-between-gps-gnss-santosh-kumar-bhoda/>
 - <https://globalgpsystems.com/gnss/the-difference-between-gnss-and-gps-explained/#:~:text=Number%20of%20Satellites%20and%20Accuracy&text=Due%20to%20the%20larger%20number.of%20any%20in,terference%20or%20obstructions.>

4.2 Data Collection using Smartphones (Global Positioning System)

4.2.1 Overall Data Collection Process




Figure 2 - Process of Data Collection

The collection of urban trees served as the main dataset for this example. Data collection followed a systematic technique, as shown in Figure 3. At first, the data-gathering forms were created using the KoBoToolBox application. Later on, these forms were connected with the ODK data gathering application, which is available for download on the Google Play Store. The data-gathering approach entailed performing field surveys utilizing the ODK program and the associated data collection forms. After gathering all the essential data, it was downloaded and imported into the QGIS application for data cleaning, processing, analysis, and mapping, if needed. This is a comprehensive overview of the complete process used to acquire data. In the next part, all the specifics are explained for each data type in data collection, accompanied by relevant photos and information.

Alternative Data Collection Methods:

KoBoToolbox & KoBoCollect: Utilize KoBoToolbox for both form creation and data collection by designing forms directly within the KoBoCollect mobile app. This approach streamlines the process by eliminating the need for integration with external applications.

ODK Build & ODK Collect: Design custom data collection forms using ODK Build, a user-friendly form designer tool, and collect data in the field using ODK Collect. This method offers flexibility in form design and customization while leveraging the robust data collection capabilities of ODK Collect.

Paper-Based Surveys: In scenarios where digital data collection tools are not feasible, traditional paper-based surveys can be employed. Design paper forms to capture relevant tree data and manually record observations in the field. Once completed, data can be transcribed into digital format for analysis.

Mobile Apps with GPS Functionality: Explore alternative mobile applications with GPS functionality for data collection, such as GeoODK Collect or Epicollect5. These apps offer similar features to ODK Collect but may have different user interfaces and additional functionalities.

Crowdsourcing Platforms: Consider leveraging crowdsourcing platforms like OpenStreetMap (OSM) for tree mapping initiatives. Engage volunteers and community members to contribute tree data through OSM-based mapping projects, fostering collaboration and community involvement.

Alternative Mobile Application for Data Collection:

App	Platform	Text	Photo	Audio	Video	Shapefile
ODK Collect	Android	✓	✓	✓	✓	✗
KoBoCollect	Android	✓	✓	✓	✓	✗
GeoODK Collect	Android	✓	✓	✓	✓	✗
Epicollect5	Android, iOS	✓	✓	✓	✓	✗
OpenMapKit	Android	✓	✓	✓	✓	✗
Fulcrum	Android, iOS	✓	✓	✓	✓	✗
iFormBuilder	Android, iOS, Web	✓	✓	✓	✓	✗
SurveyCTO	Android, iOS, Web	✓	✓	✓	✓	✗
Field Data Collection	iOS, Web	✓	✓	✓	✓	✗
KoBoToolbox	Web	✓	✓	✓	✓	✗
ODK Build	Web	✓	✗	✗	✗	✗
Add to Shapefile	Android	✗	✗	✗	✗	✓
GeoPaparazzi	Android	✓	✓	✗	✗	✓

Table 2 - Other Mobile Applications for Data Collection

4.3 Steps (Mobile Phones)

4.3.1 Prepare data collection form.

Step 1

The KoBoToolbox is the platform that we used to prepare the data collection form. The following weblink and Figure 4 show the interface of the KoboTool Box application.

Web Link: <https://www.kobotoolbox.org/>



Figure 3- Interface of the Kobo Tool Box

KOBO TOOL BOX :



Kobo Toolbox is a free and open-source suite of tools for field data collection. The web KoboToolbox application allows user design complex forms, deploy and download submitted data.

KoboToolbox makes it easy to develop forms for data collection. It also has features for managing projects, visualizing data, and building complex forms.

Step 2

Prepare the account in the KoBoToolBox: To begin the process, it is essential to create an account on the KoBoToolBox application, which allows us to allocate space on their servers for storing the collected ground data. By following the provided link, you will be directed to the registration page.

- Click on the **"Create new account"** option.
- Then select "Global KoboToolbox Server" and then create an account.




Figure 4 - Create Account

Then it will prompt the following interface to appear:

The image shows a 'Create an account' form on the KoboToolbox Global Server. The form is overlaid on a background image of a dry, dusty landscape with small, round huts. The form fields include: Full name, Username, Email (with a placeholder 'name@organization.org'), Country (a dropdown menu), Sector (a dropdown menu), Organization name, Organization website, Password, and Password confirmation. A blue 'CREATE ACCOUNT' button is at the bottom. To the right of the form, there is text about the server: 'High quality data collection tools for social impact organizations working in challenging environments. For organizations that prefer data hosting in the European Union, please create an account on the EU-based server. Get started by creating a free account on our Community Plan, which includes unlimited projects, unlimited data collectors and collaborators, 5,000 submissions per month, and 1GB of file storage. Users who require more data storage, survey submissions, or features can upgrade their account at any time.' At the bottom of the form, there are links for 'Terms of service' and 'Privacy policy'.

Figure 5 - Registration Process

Provide all the necessary information and complete the account registration process. Once your account setup is complete, you will receive an email to confirm your account. Click on the received link and confirm your account. Once your email is confirmed, you will be directed to the login page where you can enter your username and password.

Step 3

Create a new data collection form: Upon successful login, you will be directed to the following interface. Then as shown in Figure 7 click the “new” option.




Figure 6 - Create a New Data Collection Form

Step 4

After clicking on the option “ new” the following interface will appear as shown in Figure 08.




Figure 7 - Interface of Create a new project

Users can use inbuilt data collection form templates if user need to use those templates by selecting the “**use a template**” option. If not select the “**Build from scratch**” option to create our template for our data collection forms. Here for this study, Build from Scratch has been selected.

Step 5

After selecting the templates, it will display the following box and then it will ask following information as Figure 9. Place the appropriate project name (1) and a short description (2) of the project. Specify the sector (3) and country (4) of the project. After that select “**Create Project (5)**”




Figure 8 - Create Project

After that following interface will appear as shown in Figure 10




Figure 9 - Project Interface

The user now can create a data collection form for data collection. To initiate this process, the user should click on **the plus symbol** as depicted in the above figure which will open the interface displayed below.




Figure 10 - Add Question Interface

Step 6

Figure 12 illustrates the interface where the user can input the first question.

6.1 So for that click on “Add Question”

6.2 Select the type as your Question type as shown in the figure below




Figure 11 - Insert Questions




Figure 12 - Selecting Type of the Questions

The objective of this example is the carry out the urban tree survey aims to assess the health and condition of trees in urban green spaces, identify environmental stressors affecting tree vitality, and inform management strategies for enhancing urban forest resilience.

In this case, the first question is designated as Tree ID. As this data collection form pertains specifically to tree data, it is essential to gather information on each tree individually. This unique identification number serves as a reference for data collection, allowing the data collector to gather information for each tree by associating it with its respective identification number. Subsequently, after the data collection process is complete, the collected data can be linked with the corresponding Geographic Information System (GIS) layers by utilizing the identification numbers. The inclusion of the identification number in both the GIS layer and the collected database ensures seamless integration between the two, enabling efficient data management and analysis.

This section serves as the user interface where the user can select the appropriate data type for the desired field. Here tree ID is to be entered as a numerical value. Therefore, it is necessary to choose the "number" data type from the provided list. Alternatively, if the user intends to capture a visual representation for this particular question, the data collection form creator should assign the data type as "photo." This will enable the data collector to access a camera option specifically designed for this question, allowing them to capture and save an image. Once the user has selected the appropriate data type for the initial question, a subsequent interface will be displayed. To proceed with entering the second question into the form, the user needs to click on the plus symbol (+), as illustrated in Figure

14. This action will provide a designated space to type the second question. The same process should be followed to prepare all the questions about road data collection.




Figure 13 - Proceed to the next Questions

Step 7

Save the project: Figure 15 shows an example data collection form for tree data collection prepared under this project. The data collection form has included **only 11 variables for this example**. After including all the questions click on the save button and then click on the close button located near the save button.




Figure 14 - Save the Project

You can preview how your survey will look after entering your questions by clicking the eye icon in the top left-hand corner. To check for errors, enter some information and click on the 'Validate' button.




Figure 15 - Preview the Project

To return to the default project page, click the Kobo icon in the upper right-hand corner. You will be redirected to the project page.




Figure 16 - Redirected to the project page

After saving the project then it will be directed to the below section as shown in Figure 18.




Figure 17 - Created Form

<p>① Under number 01, three tabs are visible: "Deployed Forms," "Draft Forms," and "Archived Forms." Currently,</p> <p>The data collection form we have prepared is listed under the "Draft" tab, indicating that it has not yet been deployed. Once deployed, it will be listed under the "Deployed" tab.</p>	<p>② The second section encompasses the metadata section of the forms, which consists of four tabs:</p> <p>"Summary of Collected Data," "Form," "Collected Data," and "Settings" for the selected form.</p> <p>Presently, only the "Settings" and "Form" tabs are active since the form has not been deployed or used for data collection. These tabs allow for customization and configuration of the form's settings and structure</p>
<p>③ The third section offers options for editing, previewing, replacing the form, and additional</p> <p>functionalities for downloading the form. Users can make modifications to the form, preview its appearance, replace it with an updated version if necessary, and access various download options</p>	<p>④ The fourth section features the "Deploy" button. Once all the necessary work on the form has been completed, clicking on the "Deploy" button will publish the form on the KoboToolbox server. This enables data collection applications to link to the form, allowing collected data to be sent directly to the KoboToolbox server through this specific form.</p>

Table 3 - Tabs in Form Interface

Step 8

8.1 The subsequent procedure entails the deployment of the meticulously prepared form. It is essential to identify the correct form from the options available under the "Draft" tab and proceed by clicking on the deploy button. Subsequently, the deployed form will be listed under the "Deploy" tab. **Once the form is deployed, it can be accessed through an external application such as Open Data Kit (ODK).**

8.2 After you deploy the form, you can select '**Online-Offline (Multiple submissions)**' under collect data. You can copy the link by clicking the 'COPY' icon to share with your team or paste the link into a search engine to open the questionnaire in a browser.




Figure 18 - Deploy

4.3.2 Download and Install ODK Application

Step 1

Download and install the ODK application: Figure 20 provides a detailed methodology that outlines the step-by-step process for downloading and installing the ODK application.




Figure 19 - Download and Install the app


ODK

Open Data Kit (ODK) is an open-source software suite designed for data collection using mobile devices. It provides a flexible and customizable platform for creating digital forms, collecting data, and managing the collected data efficiently. ODK is widely used in various fields such as research, humanitarian aid, public health, and environmental monitoring. ODK consists of several components that work together to facilitate the entire data collection process. These components include:

ODK Build: A web-based form designer that allows users to create forms using a drag-and-drop interface without requiring programming skills. It enables the easy creation of digital forms for Android devices that serves as the data collection tool. It allows field workers to download the digital forms created with ODK Build and collect data using their mobile devices, even in offline or low connectivity areas. ODK Collect supports GPS location capture, image and audio attachments, and can handle complex skip logic within forms.

ODK Aggregate: A server application that acts as a central repository for collected data. ODK Collect syncs with ODK Aggregate to upload the collected data securely. ODK Aggregate provides data management features like data storage, data export in various formats, data visualization, and user access control.

ODK Briefcase: A desktop tool that allows users to pull data from ODK Aggregate and export it to a local machine.



Step 2

Setup ODK and link prepared data collection forms to ODK application

- 1.1 The initial interface encountered upon opening the ODK application for the first time is depicted in Figure 22.
- 1.2 Subsequently, users need to click on “**Manually enter Project Details**” as shown in Figure 22.
- 1.3 The ODK application necessitates three essential pieces of information: URL, Username, and password. As illustrated in Figure 24, the URL can be obtained from the KoboToolbox platform. Additionally, after deploying all the forms, users need to navigate to the “**Collect Data**” section located at the bottom of the webpage. Within that section, there is a dropdown arrow that, when clicked, displays a list of options for linking the data collection form with other third-party applications. To proceed, users should select the “Android Application” option from the list and copy the link of the KoboToolbox platform. Subsequently, the username associated with the KoboToolbox profile, under which the data collection forms were prepared, needs to be appended to the link.
- 1.4 Then paste it in the ODK as shown in Figure 25.
- 1.5 After that, you will proceed to the new interface as shown in Figure 26. Click on “**Download Form**”.
- 1.6 After you see the form, you prepared and then follow the steps in Figure 27.




Figure 20 - Interface of the ODK







Figure 21 - ODK Details



Step 2.6




Figure 25 - Download the Form

Step 3

Data collection using ODK application: Click on “Start new form” as shown in Figure 28.




Figure 26- Collect Data

Step 4

Export data: After completing the data collection process, as shown in the figures below follow the steps.

4.1. Go to the **"Ready to Send"** tab and select all the collected data.

4.2. Click on the **"Send"** button and allow time for the sending process to complete.

4.3. Once the sending process is finished, click **"OK."**

4.4. Return to the main interface. As depicted in Figures 32 and 33, the sent data will now be displayed under the **"Sent"** tab.




Figure 27 - Data Exporting Process

Step 5

Downloading data from Kobo Toolbox: Once the data collection process is complete, follow these steps to download the collected dataset:

5.1 Proceed to the **"Data"** tab within KoboToolbox. The list of data can be found in a table as shown in figure 30.

5.2 Next, click on the **"Download"** option, and within the ensuing step, ensure that the data type selected for download is **"CSV Legacy."**

5.3 Click on the **"New Export"** option. This will generate a link (this will take some time), which you can utilize to download the data associated with the selected data collection form.

5.4 Once the link is prepared, simply click on it to initiate the download of the data for the specific data collection form.




Figure 28 - Collected Data




Figure 29 - Data Downloading




Figure 31 - Add Data to QGIS




Figure 32 - Collected Data point of trees

Step 3

To update existing data using Google My Maps, follow these steps: Access Google My Maps through this link [<https://www.google.com/mymaps>].

- c. Import the CSV file into Google My Maps by clicking on the "Import" option.
- d. Select the GPS coordinates and Tree ID from the CSV file. Once imported, the points will be displayed on the map.
- e. Click on any point to view its details, and you can edit them as needed. After editing, save the changes.
- f. You can share the map with others by using the sharing options, as shown in Figure 36




Figure 33 - Edit the Data




Figure 34 - Share the Details

4.4 Data Collection using GNSS (Global Navigation Satellite System)

Global Navigation Satellite Systems (GNSS) have revolutionized surveying and mapping by providing accurate positioning data. GNSS surveying methods employ satellite signals to determine precise coordinates, enabling professionals in various industries to carry out accurate measurements

4.4.1 Overall Data Collection Process




Figure 35 -Data Collection from GNSS

The primary difference between the Stonex S70 and S70G lies in their capabilities: the S70G is an RTK (Real-Time Kinematic) device, offering high-precision positioning with superior accuracy, ideal for demanding surveying tasks. In contrast, the S70 functions as a standard GNSS receiver, similar to the one in your mobile phone, providing basic positioning capabilities suitable for general applications.

4.4.2. S70 G Data Collection




Figure 36 - Two types of S70G

Step 01

Click on the below icon (Cube a v6) to start.



Figure 37 -Cube a v6

Step 02

2.1 - Go to the Project tab.

2.2- Click on Project Manager to create a new file.





Figure 38 -Project Manager

Step 03

Then you will get the below interface and then go to the “New”




Figure 39 - Create New File

Step 04

Then give the project name as per the study and click on next.

05:40 33%

< New Project

Project Name Sample Project ✖

Configuration Standard ▼

Configurations...

Operator

Device

Notes

Date Created 2024-05-20 05:40:23




Figure 40 -Create Project

Step 05

Then you will get this interface and click on “proj file”.

11:34 54%

New Project

Coordinate System

Coordinate systems parameters type: Local parameters

Warning: do not select the RTCM1021~1027 parameters option unless you are sure that the CORS sends them out.

Select the Reference System to use in the new project

CPj: Default

Type	Standard	
Name	Default	
Country	Unknown	Ellipsoid
Projection	Transverse Mercator	Everest-1830(1937 Adjustment)
Geoid File	---	Proj. S.F. 0.99992384

- List
- File
- Proj.
- Geoid
- Info

☐ I want to work with real/ground distances.
Bring me to the "One Point GPS Localization" after creating the project

[< Previous](#) [> Create](#)

Figure 41 - Set Coordinates

Step 06

Then you will get this interface and in there click on “**Stonex cube**”




Figure 42 -Stonex Cube

Step 07

Click on the “Coordinate” to set the coordinate system




Figure 43 - Coordinate Systems

Step 08

Click on the Coordinate System and select the import.





Figure 44 - Set the Coordinates

Step 09

9.1 – Then go to the main page and click on the “Device Tab”

9.2 – Then select on Communication





Figure 45 - Set up the Device

Step 10

Then you will see the interface below. Click on the Disconnect button first, which belongs to the previous task




Figure 46 - Disconnecting

Step 11

11.1-Then, click on the drop-down menu, select "Stonex 70G,"

11.2 - Then click on "Connect."




Figure 47 - Connect the Device

Step 12

Then go back and select the “Working mode” under the device tab




Figure 48 -Working Mode

Step 13

Select “Rover”




Figure 49 - Select Rover

Step 14

Set the following parameters:

13.1 Elev. mask: Set it between 10 and 15.

13.2 Communication mode: Select "Phone network."

The screenshot displays the 'Rover mode settings' application interface. At the top, the status bar shows the time 05:47 and a 30% battery level. The app title 'Rover mode settings' is centered in a blue header. Below the header, the 'Options' section is highlighted with a red box. It contains a text input field for 'Elev. Mask angle (0~45):' with the value '10' entered. A red circle with a white '0' and a red 'x' icon is positioned to the right of the input field. A yellow callout box labeled 'Step 14.1' points to this red circle. Below the 'Options' section is the 'Record raw data' toggle, which is currently turned off. The 'Datalink' section follows, showing 'Communication Mode:' set to 'None'. A dropdown menu is open, showing 'Phone Network' as the selected option, which is also highlighted with a red box. A yellow callout box labeled 'Step 14.2' points to this dropdown. Below the dropdown is the 'Antenna Parameters' section, which includes fields for 'Measured Height' (2.000), 'Measurement Type' (Vertical height), and 'Antenna Height' (2.076). The 'Satellite Systems' section is at the bottom, featuring a blue bar with 'Save to Configurations' and 'Apply' buttons. A numeric keypad is visible at the very bottom of the screen.

05:47 30%

Rover mode settings

Options

Elev. Mask angle (0~45): 10

Record raw data

Datalink

Communication Mode: None

Phone Network

Antenna Parameters

Measured Height: 2.000

Measurement Type: Vertical height

Antenna Height: 2.076

Satellite Systems

Save to Configurations Apply

1 2 3 -

4 5 6 _

7 8 9 <X>

, 0 . →|

Step 14.1

Step 14.2

Figure 50 - Setting the Rover

Step 15:

then enable the following “satellite system” options and select apply.

14:20 9%

Rover mode settings

Options

Elev. Mask angle (0~45):

Record raw data ☐

Datalink

Communication Mode:

Phone Network

Antenna Parameters

Measured Height:

Measurement Type:

Antenna Height:

Satellite Systems

GPS enable ☒

GLONASS enable ☒

BEIDOU enable ☐

GALILEO enable ☐

QZSS enable ☐

Save to Configurations Apply

Figure 51 -Enable the GPS

Step 16

Then, this interface will appear. Click on "Mount Point" and select "Get Access Point."

05:47 30%

< Send diff. from controller

Connect Mode:

☐ TCP Client ☒ NTRIP

CORS Settings

Name: LKA: Suleco

IP: 222.165.151.170

Port: 60606

Notify when base coordinates change: ☒

CORS Account

User: LBSUOM1

Password:

Show password ☐

MountPoint:

Corrections

CLMB_MSM4

GET ACCESS POINT

Receive:

START OK

Figure 52 -Get Access Point

Step 17

Then, from this drop-down menu, you need to select the point. Since this project is done in Colombo, select "Colombo," and always select "MSM4"




Figure 53 -Select the point

Step 18

Select Apply

05:51 29%

Rover mode settings

Elev. Mask angle (0~45):

Record raw data

Datalink

Communication Mode: Phone Network

Phone Network

Antenna Parameters

Measured Height: 2.000

Measurement Type: Vertical height

Antenna Height: 2.076

Satellite Systems

GPS enable

GLONASS enable

BEIDOU enable

GALILEO enable

QZSS enable

SBAS enable

Save to Configurations

Apply

Figure 54 - Finalize the Rover Setup

Step 19

Then it will direct to the main page. Then click on “Antenna Type”





Figure 55 -Setup the Antenna

Step 20

Then, select the antenna type as "S70G on a tablet." The other option is "on pole," but for this study, since it connects to the tablet, select the "S70G on tablet" option

05:53 29%

< Antenna Type

Ext. antenna type:

Stonex SA15 (S70G - ON TABLET) ▾

Brand : Stonex

Model : SA15 (S70G - ON TABLET)

L1 offset from ARP : 65.000 [mm]

L2 offset from ARP : 65.000 [mm]

APPLY

Figure 56 - Select the Antenna Type

Step 21

Then, go back to the main page

21.1 – Go to the “point” tab

21.2 -Select point Survey




Figure 57 - Point Survey

Step 22

Then this interface will appear. Through the below icon, you can get the open street map.




Figure 58 -Survey Map

Step 22

Click “Topo Point”




Figure 59 -Topo Point

Step 23:

Then you will be directed to the "Topo Point Settings."

- Solution Limit: Set it to "Fixed."
- HRMS Setting: Set this according to your preference. This setting determines the accuracy level for data collection. Data will only be collected if it meets the specified accuracy level.
- If you do not need high accuracy, you can set the Solution Limit to "Float," or if you do not want to enforce any accuracy requirements, tick the "Ignore this quality check" option.
- Select save

07:01 12%

Topo Point Settings

☐ Quick mode

Quality Checks

Solution Limit: FIXED

HRMS Limit: 0.020
☐ Ignore this quality check

VRMS Limit: 0.020
☐ Ignore this quality check

PDOP limit: 2.0
☐ Ignore this quality check

Diff. corr. delay limit [s]: 5.0

Record Options

Average GPS Count: 1

Averaging delay [s]: 15

SAVE

Figure 60 - Quality Check

Step 24

Then you will be directed to this page and select the below icons.




Figure 61 -Map Page

Step 25

Then, click on the icon below to start collecting data. While collecting data, ensure that the "H & V" indicators are green, indicating high accuracy.



Figure 62 -Get the point

Then select ok

Figure 63 - Save the Point

Step 27

Similarly, you can collect the data. For this project, we conducted a survey on trees at the University of Moratuwa.

Click on the below icon to see the collected data.



Figure 64- Collected Point

This is the point Library



11:16 							
<div>  <div>Point Library</div> </div>							
<div> <div></div> <div></div> <div></div> </div>		<div> <div>Point Name or Code</div> <div></div> </div>					<div>Q</div>
<div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> </div>				<div> <div>↓ A</div> <div>↑ Z</div> <div>↓ 30</div> <div>↑ 30</div> <div>↓ 1</div> <div>↑ 1</div> </div>			
<input type="checkbox"/>	No.	Name	P	G	Northing	Easting	Elevation
<input type="checkbox"/>	#22	Ahala3			477501.751	403448.117	26.171
<input type="checkbox"/>	#21	Araliya			477499.599	403473.988	25.634
<input type="checkbox"/>	#20	Ahala1			477499.284	403493.586	26.912
<input type="checkbox"/>	#19	Kohomba			477501.593	403508.043	26.809
<input type="checkbox"/>	#18	mango			477522.386	403513.049	23.875
<input type="checkbox"/>	#17	Na			477539.031	403514.112	20.782
<input type="checkbox"/>	#16	Ahala			477549.791	403516.919	21.169
<input type="checkbox"/>	#15	Kottamba8			477557.573	403514.051	22.163
<input type="checkbox"/>	#14	Kottamba7			477558.787	403506.889	23.564
<input type="checkbox"/>	#13	Kottamba6			477558.077	403497.792	22.579
<input type="checkbox"/>	#12	Kottamba5			477561.740	403487.256	26.940
<input type="checkbox"/>	#11	Pihibiya6			477561.292	403483.096	23.902
<input type="checkbox"/>	#10	Pihibiya5			477561.728	403474.406	26.059
<input type="checkbox"/>	#9	Kottamba3			477559.665	403462.038	20.221
<input type="checkbox"/>	#8	Pihibiya4			477559.791	403456.216	19.324
<input type="checkbox"/>	#7	Pihibiya3			477560.487	403446.959	20.040
<input type="checkbox"/>	#6	Pihibiya2			477563.593	403442.551	22.382
<input type="checkbox"/>	#5	Pihibiya			477563.022	403435.859	20.430
<div> <div>+</div> <div>Add</div> </div>		<div> <div></div> <div>Edit</div> </div>		<div> <div></div> <div>Details</div> </div>		<div> <div></div> <div>Tools</div> </div>	
<div> <div></div> <div>Import</div> </div>		<div> <div></div> <div>Delete</div> </div>		<div> <div></div> <div>Delete all</div> </div>		<div> <div></div> <div>OK</div> </div>	

Figure 65 - Point Library

Step 28

Again, go to the main Project tab and click on the export icon to export the data.




Figure 66 - Export Data

Step 29

29.1 -Tick the "Share after exporting" option, which will allow you to share the data through different platforms. If not, the file will only be saved to the device.

29.2 -Then, select "Export."

12:16

Export File

Export Path /storage/emulated/0/StonexCube/Export/

File Name Treemapping

Data file Treemapping.PD

File type Name,Easting,Northing,Elevation,Code

☒ Share after exporting

Step 28.1



Figure 67 -Click Export

Step 30

Select the Export Type




Figure 68 - Export Formats

Step 31
Click Ok




Figure 69 -User Action

Step 32

Share through any platform




Figure 70 -Share

4.4.3.S70 Data Collection

Step 01

Click on the below icon (Cube a v6) to start.



Figure 71 -Cube a v6

Step 02

2.1 - Go to the Project tab.

2.2- Click on Project Manager to create a new file




Figure 72 -Project Manager

Step 03

Then you will get the below interface and then go to the “New”




Figure 73 -Create New File

Step 04

Then give the project name as per the study.

The screenshot shows a mobile application interface for creating a new project. The title bar is blue with a back arrow and the text "New Project". The status bar at the top shows the time 11:34, signal strength, and 55% battery. The form contains the following elements:


- Project Name:** A text input field containing "Treemapping" with a red asterisk icon on the right.
- Enable GIS:** A toggle switch currently turned off, with a red circle containing the number "0" above it.
- Configuration:** A dropdown menu showing "Standard" with a downward arrow icon.
- Configurations...:** A blue button with a pencil icon and the text "Configurations...".
- Operator:** An empty text input field.
- Device:** An empty text input field.
- Notes:** An empty text input field.
- Date Created:** A text input field containing the timestamp "2024-05-20 11:33:41".

The bottom navigation bar is blue and contains two buttons: "Cancel" with a red 'X' icon and "Next" with a right arrow icon.

Figure 74 --Create Project

Step 05

Here, compared to S70G, for S70, you need to enable the GIS option.



The screenshot shows a mobile application interface for creating a new project. The title bar is blue with a back arrow and the text "New Project". The status bar at the top shows the time 11:34, signal strength, and 54% battery. The form contains the following fields:

- Project Name:** A text input field containing "Treemapping" with a red asterisk icon on the right.
- Enable GIS:** A toggle switch that is currently turned on (green), highlighted by a red rectangular box.
- Configuration:** A dropdown menu showing "Standard" with a downward arrow icon.
- Configurations...:** A blue button with a pencil icon and the text "Configurations...".
- Operator:** An empty text input field.
- Device:** An empty text input field.
- Notes:** An empty text input field.
- Date Created:** A text input field containing the timestamp "2024-05-20 11:33:41".

At the bottom, there is a blue bar with two buttons: "Cancel" (with a red X icon) and "Next" (with a right arrow icon).


Figure 75 -Enable GIS

Step 06

Then you will get this interface and click on “file”.

11:34

54%

 New Project

Coordinate System

Coordinate systems parameters type:

Local parameters

Warning: do not select the RTCM1021~1027 parameters option unless you are sure that the CORS sends them out.

Select the Reference System to use in the new project

CPj: Default

Type

Standard

Name

Default

Country

Unknown

Projection

Transverse Mercator


Geoid File


Ellipsoid


Everest-1830(1937 Adjustment)


Proj. S.F.


0.99992384

 List

 File

 Proj.

 Geoid

 Info

☐ I want to work with real/ground distances.
Bring me to the "One Point GPS Localization" after creating the project

 Previous

 Create

Figure 76 -Set Coordinates

Step 07

Then you will get this interface and in there click on “**Stonex cube**”




Figure 77 -Stonex Cube

Step 08

Click on the “Coordinate” to set the coordinate system.




Figure 78 - Coordinate Systems

Step 09

Click on the Coordinate System and select the import.




Figure 79 -Set the Coordinates

Step 10

Click on "Edit" and give a name for your study. Under "Tree Mapping," we are going to do Ahala tree mapping at the University of Moratuwa.

11:36 52%

Activate GIS Feature Set Repository

Feature sets repository

DEMO1-SIMPLE1

Edit Add Clone Delete

Repository description

Simple sample

Repository contents

Simple1

Simple point with name, code and one numeric attributes

Compatible geometries

Point

Cancel OK

Figure 80 - Tree Mapping Sub-Category

Step 11

Give the name

The screenshot shows a mobile application interface. At the top, a status bar displays the time 11:39, signal strength, location, and battery level at 49%. Below this is a blue header bar with a back arrow on the left and the text "GIS Feature Set Repository name." in the center. Under the header, the instruction "Enter a name for the GIS Feature Set Repository." is displayed. A text input field contains the text "20240520_1138". To the right of the input field is a red circular button with a white 'X' icon. At the bottom of the screen, a virtual keyboard is visible, featuring a blue bar with "Cancel" and "OK" buttons, and a standard QWERTY keyboard layout with a blue checkmark button on the right.

Figure 81 -Naming

Then it will appear as below figures:




Figure 82 -Activate GIS Features

Step 12

Click on “Edit”

The screenshot shows a mobile application interface for editing a GIS Feature Set Repository. At the top, the status bar displays the time 11:39, a camera icon, and battery level 48%. The app header is blue with a back arrow and the title 'Edit GIS Feature Set Repository'. Below the header, there are two input fields: 'Repository name' with the text 'Ahalatree_mapping' and 'Repository description' with the text 'No Description'. A section titled 'Repository contents' in a grey bar contains a yellow card with the text 'Rename Me', 'No Description', 'Compatible geometries', and a radio button selected next to 'Point'. At the bottom, there are five blue buttons: 'EDIT', 'ADD', 'DELETE', 'CANCEL', and 'OK'.

11:39 48%

< Edit GIS Feature Set Repository

Repository name

Ahalatree_mapping

Repository description

No Description

Repository contents

Rename Me
No Description
Compatible geometries
☒ Point

EDIT ADD DELETE

CANCEL OK

Figure 83 -Edit

Step 13

Then, give a name for the details you want to include in the survey. As shown in the figures (84,85,86,87), by clicking on **"Add,"** you can include additional details.

11:40 48%

Edit GIS Feature Set

Name

Tree

Description

No Description

Options

☐ Autofill from last stored/collected GIS Feature Set data.

Compatible geometries

☒ ☐ ☐ ☐ ☐

Feature List

Name: **F1**
Prompt: **F1**
Type: TEXT
Interpretation: GENERIC
Flags:

ADD	EDIT	CLONE	DELETE
MOVE UP	MOVE DOWN	CANCEL	OK

Figure 84 -ADD

11:41
47%

Edit GIS Feature

DB field name

Color

Prompt

Color

Data type

TEXT

Width

50

Decimals

0

Data interpretation

GENERIC

Lookup list

None

Default value

☒ Visible

☐ Mandatory

☒ User editable

☐ Allow user to add custom values

☐ Auto-increment

Cancel

OK

Figure 85 -Edit GIS Features

11:42

46%

<

Edit GIS Feature

DB field name

Height

Prompt

Height

Data type

DECIMAL

▼

Width

20

▼

Decimals

0

▼

Data interpretation

GENERIC

▼

Lookup list

None

▼

Default value

☒ Visible

☐ Mandatory

☒ User editable

☐ Allow user to add custom values

☐ Auto-increment

✕ Cancel

✓ OK

Figure 86 - Edit GIS Features

Step 14

Click Ok

11:45

43%

<

Edit GIS Feature Set

Name

Tree






Description

No Description

Options

☐ Autofill from last stored/collected GIS Feature Set data.

Compatible geometries

☒  ☐  ☐  ☐  ☐ 

<<

Feature List







>>

Name: **F1**

Prompt: **F1**

Type: TEXT

Interpretation: GENERIC







Flags:      

Name: **Color**

Prompt: **Color**

Type: TEXT

Interpretation: GENERIC







Flags:      

Name: **Height**

Prompt: **Height**

Type: DECIMAL

Interpretation: GENERIC

Flags:      

Name: **Specialnot**

Prompt: **Specialnot**

Type: TEXT

ADD

EDIT

CLONE

DELETE

MOVE UP

MOVE DOWN

CANCEL

OK

Figure 88 -Set GIS Features

Step 15

Click Yes




Figure 89 – User Action Required

Step 16

Click Ok

11:45

Edit GIS Feature Set Repository

Repository name

Ahlatree_mapping

Repository description

No Description

Repository contents

Tree

No Description

Compatible geometries

Point

EDIT ADD DELETE

CANCEL OK

Figure 90 -Set Repository

Step 17

Click Yes




Figure 91 -User Action

Step 18

Click Ok

11:45 43%

Edit GIS Feature Set Repository

Repository name

Ahalatree_mapping

Repository description

No Description

Repository contents

Tree

No Description

Compatible geometries

Point

EDIT ADD DELETE

CANCEL OK

Figure 92 -Set Gis and Repository

Step 19

18.1 – Then go to the main page and click on the “Device Tab”

18.2 – Then select on Communication




Figure 93 -Set up the Device

Step 20

Then you will see the interface below. Click on the Disconnect button first, which belongs to the previous task




Figure 94 - Disconnecting

Step 21

20.1-Then, click on the drop-down menu, select "Stonex 70G,"

20.2 - Then click on "Connect."




Figure 95 -Connect the Device

Step 22

Then go back and select the “Working mode” under the device tab




Figure 96 -Working Mode

Step 23

Select “Rover”




Figure 97 -Rover

Step 24

Set the following parameters: Elev. mask: Set it between 10 and 15.

The screenshot shows the 'Rover mode settings' application interface. At the top, the status bar displays the time 11:48 and battery level at 40%. The app title 'Rover mode settings' is centered in a blue header. Below the header, the 'Options' section is highlighted with a red rectangular border. It contains two settings: 'Elev. Mask angle (0~45):' with a numeric input field set to '5' and a red 'x' icon, and 'Record raw data' with a toggle switch currently set to '0'. Below 'Options' is the 'Datalink' section, featuring a 'Communication Mode:' dropdown menu set to 'None' and a large blue button labeled 'None'. The 'Antenna Parameters' section follows, with three input fields: 'Measured Height:' set to '2.000', 'Measurement Type:' set to 'Vertical height' with a dropdown arrow, and 'Antenna Height:' set to '2.000'. The 'Satellite Systems' section at the bottom lists five satellite systems with corresponding toggle switches: 'GPS enable' (green, on), 'GLONASS enable' (green, on), 'BEIDOU enable' (red, off), 'GALILEO enable' (red, off), and 'QZSS enable' (red, off). A blue footer bar at the very bottom contains two buttons: 'Save to Configurations' with a document icon and 'Apply' with a checkmark icon.

Figure 98- Set the parameters

Step 25

Enable the following “satellite system” options and select apply

11:49 40%

Rover mode settings

Elev. Mask angle (0~45): 10

Record raw data 0

Datalink

Communication Mode: None

None

Antenna Parameters

Measured Height: 2.000

Measurement Type: Vertical height

Antenna Height: 2.000

Satellite Systems

GPS enable I

GLONASS enable I

BEIDOU enable I

GALILEO enable I

QZSS enable 0

SBAS enable I

Save to Configurations Apply

Figure 99- Enable the following satellite system

Step 26

Then, go back to the main page

25.1 – Go to the “point” tab

25.2 -Select point Survey




Figure 100-Point Survey

Step 27

Then you will be directed to this page and select the below icons.




Figure 101 -Map page

Step 28

Then, click on the icon below to start collecting data. While collecting data, ensure that the "H & V" indicators are green, indicating high accuracy.




Figure 102 --Get the point

Step 29

Then select ok

12:10

23%

<

Topo Point

Name:

2

Code:

Measured Height:

2.000

Measurement Type:

Vertical height

▼

Measured point info

Record	<1/1> Collected
Solution	(13/13) SINGLE
HRMS	8.04301
VRMS	12.00000
PDOP	1.5
GDOP	99.0
Northing	477516.55750
Easting	403436.14638
Elev.	42.38565
Delay	0.0
Dist. from prev.	9.8685
Longitude	079°54'00.519000"
Latitude	006°47'48.075600"
Altitude	-62.00000
Local Time	12:10:33
Local Date	2024-05-20
Base Distance	None

Photo And Sketch

✓

OK

Figure 103-Topo point

Step 30
Add descriptions

12:11 ● 📹 🔍 22%

< Enter GIS Attributes

Use the arrows to select a GIS Feature Class
then enter the Feature Values

< Tree >
No Description
1 of 1

F1

Color

Height

Specialnot

✕ Cancel ✓ OK

Figure 104- Add description

12:12

22%

<

Enter GIS Attributes

Use the arrows to select a GIS Feature Class
then enter the Feature Values

<

Tree

No Description

1 of 1

>

F1

✕

Color

Dark green

✕

Height

10

✕

Specialnot

it looks healthy

✕

✕ Cancel

✓ OK

Figure 105-Enter GIS attributes

Step 31

Similarly, you can collect the data. For this project, we conducted a survey on trees at the University of Moratuwa.

Click on the below icon to see the collected data.




Figure 106 - Collect the data

This is the point Library.

13:40

Point Library

Point Name or Code

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

☒

A
Z

Z
A

30

1

1

30

z

z

<input type="checkbox"/>	No.	Name	P	G	Northing	Easting	Elevation
<input type="checkbox"/>	#8	Tree8		G	477551.258	403511.195	30.884
<input type="checkbox"/>	#7	Tree7		G	477567.452	403474.947	29.984
<input type="checkbox"/>	#6	Tree6		G	477571.112	403407.853	26.786
<input type="checkbox"/>	#5	Tree5		G	477576.960	403334.038	22.787
<input type="checkbox"/>	#4	Tree4		G	477542.727	403295.838	27.588
<input type="checkbox"/>	#3	Tree3		G	477515.580	403334.959	35.988
<input type="checkbox"/>	#2	Tree2		G	477505.335	403404.086	38.086
<input type="checkbox"/>	#1	Tree1		G	477510.000	403413.233	40.386

Add

Edit

Details

Tools

Import

Delete

Delete all

OK

Figure 107- Point Library

Step 32

Again, go to the main Project tab and click on the export icon to export the data.




Figure 108 -Export Data

Step 33

32.1 -Tick the "Share after exporting" option, which will allow you to share the data through different platforms. If not, the file will only be saved to the device.

32.2 -Then, select "Export."

13:41 45%


< Export File >

Export Path /storage/emulated/0/StonexCube/Export/ >

File Name Treemapping1

Data file Treemapping1.PD ▾

File type Raw measurement data format (csv) ▾

☒ Share after exporting 

Step 32.1

Step 32.2



 Options  Export

Figure 109 -Exporting

Step 34:

Select the Export Type (Here you can export the shapefiles)




Figure 110 -Export Format

13:45

42%

<

GIS Data Export

Select a GIS repository set to export

Ahalatree_mapping

Select a geometry type to export

Point

Based on your selection, the following will be exported:

Geometry type	Item count
Point	8
<i>Polyline</i>	0
<i>Polygon</i>	0
<i>Arc of circle</i>	0
<i>Circle</i>	0

Reference system of output files:

Job ref.sys. - Grid coords

✕ Cancel

✓ Export

Figure 111 -Export

5. MEASURE AND MAP NOISE POLLUTION WITH MOBILE PHONE

5.1 Introduction

Noise pollution, which is frequently ignored, has a major impact on human health and the environment. Urbanization, industrial activity, and transportation are major contributors to growing noise levels, which can cause stress, hearing loss, and other health problems. Addressing noise pollution is critical to building healthier, more livable communities.

With the advancement of technology, the general population may now measure and map noise pollution using their mobile devices. Modern smartphones are equipped with sensitive microphones and strong processors, allowing them to serve as portable noise meters. Various applications use these characteristics to assist users monitor noise levels in their surroundings, allowing them to make educated decisions.


This section of the book will walk you through the process of measuring and mapping noise pollution using your mobile device. It will go over how to choose the right apps, how to take precise measurements, how to interpret data, and how to create noise maps. By the end of this book, you will have the knowledge and skills you need to help raise awareness and reduce noise pollution in your community.

Monitoring noise levels is important. Monitoring noise pollution is critical for a variety of reasons.

- **Health Protection:** By evaluating noise levels, people and communities may decrease exposure and safeguard their health.
- **Understanding noise patterns** is useful in urban planning and environmental management.
- **Regulation and Policy:** Accurate noise data facilitates the development and implementation of noise rules and policies.
- **Public Awareness:** Educating the public about noise pollution and its effects can lead to more community-led noise-reduction measures.

5.2 Overview of Mobile Apps for Noise Measurement

Mobile apps have made it easier to measure noise pollution accurately and conveniently. These apps leverage the microphone of your smartphone to capture sound levels in decibels (dB) and provide valuable data for noise monitoring and analysis. One such app is NoiseCapture, which is popular for its comprehensive features and ease of use.



Noise Capture is an open-source mobile application designed to measure environmental noise levels. It is available on the Google Play Store and is widely used for its accuracy and user-friendly interface

Figure 112 -Noise Capture App

5.2.1 Features of Noise Capture App:

- **Accurate Noise Measurement:** The app measures sound levels in real time using your phone's microphone.
- **Data Logging:** It allows you to log noise data over time, providing a detailed record of noise levels.
- **GPS Integration:** Noise Capture integrates with GPS to tag noise measurements with geographic coordinates, enabling the creation of noise maps.
- **User-Friendly Interface:** The app is easy to navigate, making it accessible for both beginners and experienced users.
- **Data Sharing:** You can share your noise measurements.
- **Graphical Analysis:** The app provides graphical representations of noise data, helping users visualize noise patterns.

5.2.3 Architecture Diagram and Workflow




Figure 113 - Work Process

Overview of Other Mobile Apps for Measuring Noise Pollution

App	Android	IOS	Key features
Sound Meter	✓		Real-time noise measurement, sound level charts, calibration.
Decibel X	✓	✓	Real-time noise measurement, spectrum analyzer, data logging, calibration, exporting data, and sharing options.
NIOSH Sound Level Meter		✓	Accurate noise measurement, occupational noise exposure assessment, real-time data, and reporting features.

Selecting the Right App for Your Needs

- Accuracy: Look for apps with good reviews and those that offer calibration features.
- Ease of Use: Select an app with an intuitive interface and clear instructions.
- Additional Features: Depending on your needs, you may require features like data logging, GPS integration, or data sharing.
- Platform Compatibility: Ensure the app is available for your mobile operating system (Android or iOS).

5.3 Steps

Step 1: Download and Install the Noise Capture Application

Figure 116 provides a detailed methodology that outlines the step-by-step process for downloading and installing the application.






Figure 114 - Install the app


Step 2: Open the App and Set Up

Once you have downloaded and installed the NoiseCapture application, follow these steps to set it up. Figure 117 guides this process.







6. Select Acknowledge




4. Give the location permission



5. Give the microphone permission



7. Set the location Access



8. Select "Yes I understand"

Figure 115 - Setup the app

Step 3: Start Recording

3.1 – Identify the interface

Once the Noise Capture app is set up, familiarize yourself with the app's interface. The main interface includes three main tabs: Spectrum, Spectrogram, and Map. Each tab provides different functionalities to help you record and analyze noise levels effectively.

- **Spectrum:** The Spectrum tab displays real-time noise level measurements in decibels (dB). It shows a bar graph indicating the noise levels over time.
- **Spectrogram:** The Spectrogram tab provides a visual representation of the noise frequency spectrum over time. It shows how the sound frequency components change, with different colors representing different intensity levels. The graph represents two dimensions. The horizontal axis shows the time, while the vertical axis shows the frequency, and the color shows the dB level.
- **Map:** The Map tab displays your current location and geo-tagged noise levels. It shows where noise measurements are being taken and provides a spatial view of noise pollution.




Figure 116 -3 Main Tabs

3.2 – Start Recording

First, start the recording by clicking the recording icon shown below.




Figure 117. Recording

Step 4: Once finished with the recording click on the below icon to stop the recording.




Figure 118 -Stop the Recording

Step 5: Add Description and press validate.





Figure 119 -Validate

Then you can view the results as shown in the figure



Noise Indicator

Mean Noise Level

Noise Exposure Distribution

Mean Noise Spectrum Chart

Figure 120 -Result

Step 6 – Map features

Click on "Show Map" to visualize your location and access the editing features for your map.





Figure 121 -Map Features

Step 7 – Export Data


To export the data, follow the below steps



What is a Decibel (dB)?



A decibel (dB) is a unit of measurement that indicates the intensity of a sound. It is a logarithmic scale used to describe sound pressure levels, where each 10 dB increase represents a tenfold increase in sound intensity.



Noise Standards for Specific Locations:

Various organizations have established guidelines and standards for acceptable noise levels in different environments. These standards aim to protect public health and welfare by minimizing noise pollution.

- World Health Organization (WHO) Guidelines:
https://www.ruidos.org/Noise/WHO_Noise_guidelines_4.html#:~:text=To%20avoid%20hearing%20impairment%20in,field%20equivalent%20sound%20pressure%20levels.
- Occupational Safety and Health Administration (OSHA) Standards
<https://www.osha.gov/noise/exposure-controls>
- Environmental Protection Agency (EPA) Recommendations :
<https://www.epa.gov/archive/epa/aboutepa/epa-identifies-noise-levels-affecting-health-and-welfare.html#:~:text=The%20document%20identifies%20a%2024,preventing%20activity%20interference%20and%20annoyance.>

Step 8 – Add Data into QGIS

1. Start QGIS on your computer.
2. Go to the Layer menu.
3. Select Add Layer, then choose Add Vector Layer.
4. In the dialog that opens, set the Source type to File.
5. Click Browse to locate your **GeoJSON** file on your computer.
6. Select the **GeoJSON** file and click Open.
7. Finally, click Add to load the GeoJSON file into QGIS.







Figure 123 - Add to QGIS

Step 9 – Categorize the data.

1. Go to properties in the data and select "Graduated" in the Symbology panel.
2. Choose the leq_mean (leq_mean appears to be the mean equivalent continuous sound level, which is a common metric used in noise studies to represent average noise levels over a specified period) field as the value to be used for the classification.
3. Select a Color Ramp that will represent the range of noise levels.
4. Classify the data by clicking the "Classify" button.
5. Apply the settings and visualize the data on the map.




Figure 124- Add Symbology

AFTERWORD

This guidebook represents a step toward demystifying GNSS and smartphone-based spatial data collection for a broad audience—from students to seasoned practitioners. By combining clear instructions, practical examples, and real-world applications, it equips users with the tools and confidence to apply geospatial technologies in diverse fields.

As spatial data becomes increasingly central to planning, monitoring, and decision-making, the ability to accurately collect and analyze such data is more critical than ever. We hope this book empowers readers to adopt modern methods and think critically about how geospatial tools can drive meaningful change in both academic and professional contexts.



lbs2its.net



ISBN 978-955-9027-90-4